



GITILATEX 51631

GITI ASSA Co.

Product Description	A silicone modified acrylic emulsion paint with very good durability, workability, appearance and excellent resistance to water.
----------------------------	--

Recommended Use	As an intermediate or finish coat for use on interior of buildings, it can be applied on the concrete, plaster, brick, etc.
------------------------	---

Physical Properties

Finish and Color	Gloss, White, Cream and other colors based on order
-------------------------	---

Drying Time	At 25 °C: 40 min. ¹ Drying times are generally related to film thickness, air circulation, humidity, temperature and number of coats and will be affected correspondingly.
--------------------	--

Solids By Volume	30 ± 3% (Determined by ISO 3233)
-------------------------	----------------------------------

Theoretical Spreading Rate	6 m ² /L at 50 μ DFT
-----------------------------------	---------------------------------

Specific Gravity	1.15 ± 0.05
-------------------------	-------------

Flash Point	Non-Flammable
--------------------	---------------

Application Details

Surface Preparation	New concrete and plaster and brick: remove laitance, dust and other contaminations from the surface with wire brush or sand paper. Maintenance and repair work: remove old paint and other contaminations from the surface, old cracked area should be sealed.
----------------------------	---

Application Conditions	The surface should be completely cleaned and dried. Do not apply when relative humidity is above 85% The surface temperature should be at least 3°C above dew point to prevent condensation.in confined areas, ventilate with clean air during application to assist solvent evaporation.
-------------------------------	---

Thinner	Fresh water
----------------	-------------

Application Method	Spray (Airless or Air) ,Roller or brush application.
---------------------------	--

Typical Film Thickness	50 μ DFT
-------------------------------	----------



GITILATEX 51631

GITI ASSA Co.

**Recoating
Interval (with
others)**

At 25 °C

Minimum : 2 h

Shelf Life

12 months

**Standard
Packing Unit**

4 kg , 13 kg (plastic can)

**Health and
safety**

Do not store at temperature below 10°C or above 30°C.
Protect skin and eyes from direct contact with liquid paint. Use with adequate ventilation. Respiratory protection is recommended when applying this product in confined spaces or stagnant air.

Rev:01

Oct. 2020