



GITILATEX 54631

GITI ASSA Co.

Product Description	A silicone modified acrylic emulsion paint with very good durability, workability, appearance and excellent resistance to water.
Recommended Use	As an intermediate or finish coat for use on exterior of buildings, it can be applied on the concrete, plaster, brick, etc.

Physical Properties

Finish and Color	Mat, White, Cream and other colors based on order
Drying Time	At 25 °C: 20 min. ¹ Drying times are generally related to film thickness, air circulation, humidity, temperature and number of coats and will be affected correspondingly.
Solids By Volume	45 ± 2% (Determined by ISO 3233)
Theoretical Spreading Rate	9 m ² /L at 50 μ DFT
Specific Gravity	1.35 ± 0.05
Flash Point	Non-Flammable

Application Details

Surface Preparation	New concrete, plaster and brick: remove laitance, dust and other contaminations from the surface with wire brush or sand paper. Maintenance and repair work: remove old paint and other contaminations from the surface, old cracked area should be sealed.
Application Conditions	The surface should be completely cleaned and dried. Do not apply when relative humidity is above 85% The surface temperature should be at least 3°C above dew point to prevent condensation.in confined areas, ventilate with clean air during application to assist solvent evaporation.
Thinner	Fresh water
Application Method	Spray (Airless or Air) ,Roller or brush application.
Typical Film Thickness	50 μ DFT



GITILATEX 54631

GITI ASSA Co.

**Recoating
Interval (with
others)**

At 25 °C

Minimum : 2 h

Shelf Life

12 months

**Standard
Packing Unit**

5 kg , 15 kg (plastic can)

**Health and
safety**

Do not store at temperature below 10°C or above 30°C.
Protect skin and eyes from direct contact with liquid paint. Use with adequate ventilation. Respiratory protection is recommended when applying this product in confined spaces or stagnant air.

Rev:00

Oct. 2020